PD020100WO-Ri-300804 PCT/EP 03/112421

JC10219530881EP0311242 JC1021966 3PCT/PTC 11 APR 2005 (94)

Amended claims

- 1. Method for coding a presentation description of audio signals, comprising:
- generating a parametric description of a sound source; linking the parametric description of said sound source with the audio signal of said sound source;

characterized by

describing the wideness of a non-point sound source (LSS) by
means of said parametric description (ND1, ND2, ND3),
wherein a shape approximating said non-point sound source is
defined; and
assigning one of several decorrelations (DIS) to said nonpoint sound source in order to allow the usage of the same
audio signal for more than one non-point sound source.

- 2. Method according to claim 1, wherein separate sound sources are coded as separate audio objects and the arrangement of the sound sources in a sound scene is described by a scene description having first nodes corresponding to the separate audio objects and second nodes describing the presentation of the audio objects and wherein a second node describes the wideness of a non-point sound source and defines the presentation of said non-point sound source by multiple decorrelated point sound sources (S1, S2, S3).
 - 3. Method according to claim 1 or 2, wherein the strenght of the decorrelation (DES) of said multiple decorrelated point sound sources is assigned to said non-point sound source.
 - 4. Method according to any of claims 1 to 3, wherein the size of the defined shape is given by parameters in a 3D co-ordinate system.
 - 5. Method according to claim 4, wherein the size of the defined shape is given by an opening-angle having a vertical

35

30

5

PD020100WO-Ri-300804 PCT/EP 03/112422

and a horizontal component.

- 6. Method according to any of claims 1 to 5, wherein a complex shaped non-point sound source is divided into several non-point sound sources each having a shape (A1, A2, A3) approximating a part of said complex shaped non-point sound source and wherein the same audio signal is used for each of said several non-point sound sources.
- 7. Method for decoding a presentation description of audio signals, comprising: receiving audio signals corresponding to a sound source linked with a parametric description of said sound source; characterized by
- evaluating the parametric description (ND1, ND2, ND3) of said sound source for determining the wideness of a non-point sound source (LSS), wherein said parametric description includes a definition of a shape approximating said non-point sound source; and
- selecting one of several decorrelations (DIS) for the audio signal of said non-point sound source depending on a corresponding indication in said parametric description.
- 8. Method according to claim 7, wherein audio objects representing separate sound sources are separately decoded and a single soundtrack is composed from the decoded audio objects using a scene description having first nodes corresponding to the separate audio objects and second nodes describing the processing of the audio objects, and wherein a second node describes the wideness of a non-point sound source and defines the presentation of said non-point sound source by means of multiple decorrelated point sound sources emitting decorrelated signals.
- 9. Method according to claim 7 or 8, wherein the strenght of the decorrelation (DES) of said multiple decorrelated point sound sources is selected depending on corresponding

5

10

PD020100WO-Ri-300804 PCT/EP 03/112423

indications assigned to said non-point sound source.

- 10. Method according to any of claims 7 to 9, wherein the size of the defined shape is determined using parameters in a 3D coordinate system.
 - 11. Method according to claim 10, wherein the size of the defined shape is determined using an opening-angle having a vertical and a horizontal component.
- 12. Method according to any of claims 7 to 11, wherein several non-point sound sources shapes (A1, A2, A3) each having a shape (A1, A2, A3) approximating a part of a complex shaped non-point sound source are combined to generate an approximation of said complex shaped non-point sound source and wherein the same audio signal is used for each of said several non-point sound sources.
- 13. Apparatus for performing a method according to any of claims 1 to 12.